

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: TOPBAND TOTAL

Product code: AF9349

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Circulation cleaning of milk pipelines

1.3. Details of the supplier of the safety data sheet

Company name: Kilco (International) Ltd
Broomhouses 2 Industrial Estate
Old Glasgow Road
Lockerbie
DG11 2SD
United Kingdom

Tel: +44 (0) 157 620 5480

Email: sds@kilco.co.uk

1.4. Emergency telephone number

Emergency tel: +44 (0) 207 858 1228

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CHIP: -: R31; C: R35; N: R51/53

Classification under CLP: Skin Corr. 1A: H314; Aquatic Chronic 2: H411; -: EUH031

Most important adverse effects: Contact with acids liberates toxic gas. Causes severe burns. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

2.2. Label elements

Label elements:

Hazard statements: EUH031: Contact with acids liberates toxic gas.
H314: Causes severe skin burns and eye damage.
H411: Toxic to aquatic life with long lasting effects.

Signal words: Danger

Hazard pictograms: GHS05: Corrosion
GHS09: Environmental



SAFETY DATA SHEET

TOPBAND TOTAL

Page: 2

Precautionary statements: P260: Do not breathe dust/fumes/gas/mist/vapours/spray.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P301+330+331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.
Rinse skin with water/shower.
P304+340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P273: Avoid release to the environment.

Label elements under CHIP:

Hazard symbols: Corrosive.
Dangerous for the environment.



Risk phrases: R31: Contact with acids liberates toxic gas.
R35: Causes severe burns.
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases: S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.
S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
S61: Avoid release to the environment. Refer to special instructions / safety data sheets.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

SODIUM HYDROXIDE

EINECS	CAS	CHIP Classification	CLP Classification	Percent
215-185-5	1310-73-2	C: R35	Skin Corr. 1A: H314	30-50%

[cont...]

SAFETY DATA SHEET

TOPBAND TOTAL

Page: 3

SODIUM CARBONATE

207-838-8	497-19-8	Xi: R36	Eye Irrit. 2: H319	10-30%
-----------	----------	---------	--------------------	--------

TROCLOSENE SODIUM

220-767-7	2893-78-9	O: R8; Xn: R22; -: R31; Xi: R36/37; N: R50/53	Ox. Sol. 2: H272; Acute Tox. 4: H302; Eye Irrit. 2: H319; STOT SE 3: H335; Aquatic Chronic 1: H410; Aquatic Acute 1: H400; -: EUH031	1-10%
-----------	-----------	---	--	-------

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Mark out the contaminated area with signs and prevent access to unauthorised personnel.

[cont...]

SAFETY DATA SHEET

TOPBAND TOTAL

Page: 4

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.
Do not handle in a confined space. Avoid the formation or spread of dust in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): The identified uses for this product are detailed in Section 1.2

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

SODIUM HYDROXIDE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	-	2 mg/m3	-	-

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Respiratory protective device with particle filter.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

[cont...]

SAFETY DATA SHEET

TOPBAND TOTAL

Page: 5

9.1. Information on basic physical and chemical properties

State: Solid

Colour: White

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Soluble

Flammability limits %: lower: Not applicable.

upper: Not applicable.

Flash point°C: Not applicable.

Relative density: 1.01-1.03

pH: 12-14 (1% soln)

9.2. Other information

Other information: Not applicable.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

SODIUM HYDROXIDE

IPR	MUS	LD50	40	mg/kg
ORL	RBT	LDLO	500	mg/kg

[cont...]

SAFETY DATA SHEET

TOPBAND TOTAL

Page: 6

SODIUM CARBONATE

ORL	MUS	LD50	6600	mg/kg
ORL	RAT	LD50	4090	mg/kg
SCU	MUS	LD50	2210	mg/kg

TROCLOSENE SODIUM

ORL	RAT	LD50	1420	mg/kg
ORL	RBT	LDLO	2500	mg/kg

Relevant effects for mixture:

Effect	Route	Basis
Corrosivity	OPT INH DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Not biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: Bioaccumulation potential.

12.4. Mobility in soil

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms. Toxic to soil organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

[cont...]

SAFETY DATA SHEET

TOPBAND TOTAL

Page: 7

Section 14: Transport information

14.1. UN number

UN number: UN1759

14.2. UN proper shipping name

Shipping name: CORROSIVE SOLID, N.O.S.
(SODIUM HYDROXIDE)

14.3. Transport hazard class(es)

Transport class: 8

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: Yes

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

* indicates text in the SDS which has changed since the last revision.

This safety data sheet is prepared in accordance with Commission Regulation (EC) No 1272/2008.

Phrases used in s.2 and s.3: EUH031: Contact with acids liberates toxic gas.
H272: May intensify fire; oxidiser.
H302: Harmful if swallowed.
H314: Causes severe skin burns and eye damage.
H319: Causes serious eye irritation.

[cont...]

SAFETY DATA SHEET

TOPBAND TOTAL

Page: 8

H335: May cause respiratory irritation.

H410: Very toxic to aquatic life with long lasting effects.

H411: Toxic to aquatic life with long lasting effects.

R8: Contact with combustible material may cause fire.

R22: Harmful if swallowed.

R31: Contact with acids liberates toxic gas.

R35: Causes severe burns.

R36/37: Irritating to eyes and respiratory system.

R36: Irritating to eyes.

R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product. Kilco (International) Ltd, Registered Office: 1A Trench Road, Mallusk, Newtownabbey, Belfast, BT36 4TY. Place of Registration: Northern Ireland, Registration Number: NI3240