

**VACUUM PUMP OIL 68F** 

Page: 1

Compilation date: 24/01/2017

Revision No: 1

### Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name: VACUUM PUMP OIL 68F

Product code: A5Q

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Lubricating oil.

# 1.3. Details of the supplier of the safety data sheet

Company name: Pennine Lubricants Limited

Unit 35 Limestone Cottage Lane

Sheffield

South Yorkshire

S6 1NJ

United Kingdom

**Tel:** 0114 285 2987 **Fax:** 0114 285 2988

Email: info@penninelubes.plus.com

### 1.4. Emergency telephone number

Emergency tel: 0114 285 2987 (Office hours only)

### Section 2: Hazards identification

### 2.1. Classification of the substance or mixture

Classification under CLP: This product has no classification under CLP.

### 2.2. Label elements

Label elements: This product has no label elements.

## 2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

### Section 3: Composition/information on ingredients

#### 3.2. Mixtures

### Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Wash immediately with plenty of soap and water. **Eye contact:** Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water.

**VACUUM PUMP OIL 68F** 

Page: 2

Inhalation: Consult a doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

### 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

#### Section 5: Fire-fighting measures

#### 5.1. Extinguishing media

Extinguishing media: Carbon dioxide. Alcohol resistant foam. Dry chemical powder.

#### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

### Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Spillages may be slippery. Refer to section 8 of SDS for personal protection details. Turn

leaking containers leak-side up to prevent the escape of liquid.

#### 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method. Bund large spills using absorbent granules, sand

or earth and reclaim bulk liquid.

# 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

## 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed.

VACUUM PUMP OIL 68F

Page: 3

### 7.3. Specific end use(s)

Specific end use(s): No data available.

### Section 8: Exposure controls/personal protection

#### 8.1. Control parameters

### Workplace exposure limits:

### Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	5mg/m3	-	-	-

#### **DNEL/PNEC Values**

**DNEL / PNEC** No data available.

#### 8.2. Exposure controls

Respiratory protection: Respiratory protection not required.

Hand protection: Gloves (oil-resistant).

Eye protection: Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

### Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

State: Liquid
Colour: Red

Odour: Characteristic odour

Evaporation rate: Negligible

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Insoluble

Also soluble in: Most organic solvents.

Viscosity: Viscous

Kinematic viscosity: 68

Viscosity test method: Kinematic Viscosity at 40C (cSt)

Boiling point/range°C: >250 Flash point°C: >200

Relative density: 0.88

# 9.2. Other information

Other information: No data available.

### Section 10: Stability and reactivity

### 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

**VACUUM PUMP OIL 68F** 

Page: 4

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

### **Section 11: Toxicological information**

#### 11.1. Information on toxicological effects

Toxicity values: No data available.

Symptoms / routes of exposure

**Skin contact:** There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness. **Ingestion:** There may be irritation of the throat.

Inhalation: No symptoms.

## **Section 12: Ecological information**

#### 12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Inherently biodegradable

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

**VACUUM PUMP OIL 68F** 

Page: 5

### **Section 13: Disposal considerations**

#### 13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

Waste code number: 13 02 05

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

## **Section 14: Transport information**

Transport class: This product does not require a classification for transport.

## **Section 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

## 15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

### **Section 16: Other information**

#### Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

\* indicates text in the SDS which has changed since the last revision.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.